



**High Frequency
Circuit Materials**

Rogers Corporation
Microwave Materials Division
100 S. Roosevelt Avenue
Chandler, AZ 85226 U.S.A.
Tel: 480 961-1382
Fax: 480 961-4533
Website: [http://www.rogers-corp.com/mwu/
litmwu@rogers-corp.com](http://www.rogers-corp.com/mwu/litmwu@rogers-corp.com)

RT/duroid® 5880

Glass Microfiber Reinforced Polytetrafluoroethylene Composite

RT/duroid® 5880 glass microfiber reinforced PTFE composite is designed for exacting stripline and microstrip circuit applications.

Glass reinforcing microfibers are randomly oriented to maximize benefits of fiber reinforcement in the directions most valuable to circuit producers and in the final circuit application.

The dielectric constant of RT/duroid 5880 laminates is uniform from panel to panel and is constant over a wide frequency range. Its low dissipation factor extends the usefulness of RT/duroid 5880 to Ku-band and above.

RT/duroid 5880 laminate is easily cut, sheared and machined to shape. It has excellent dimensional stability and is resistant to all solvents and reagents, hot or cold, normally used in etching printed circuits or in plating edges and holes.

Normally supplied as a laminate with electrodeposited copper of 1/4 to 2 ounces/ ft.² on both sides, RT/duroid 5880 composites can also be clad with rolled copper foil for more critical electrical applications. Cladding with aluminum, copper or brass plate may also be specified.

When ordering RT/duroid 5880 laminates, it is important to specify dielectric thickness, tolerance, rolled or electrodeposited copper foil, and weight of copper foil required.

(See reverse for product data)

RT/duroid 5880 Properties:

PROPERTY	TYPICAL VALUE			DIRECTION	UNITS	CONDITION	TEST METHOD
Dielectric Constant, ϵ_r	2.20			Z	---	C24/23/50	1 MHz IPC-TM-650 2.5.5.3
	2.20 \pm 0.02 spec.			Z		C24/23/50	10 GHz IPC-TM-650 2.5.5.5
Dissipation Factor, $\tan \delta$	0.0004			Z	---	C24/23/50	1 MHz IPC-TM-650 2.5.5.3
	0.0009			Z		C24/23/50	10 GHz IPC-TM-650 2.5.5.5
Volume Resistivity	2 X 10 ⁷			Z	Mohm cm	C93/35/90	ASTM D257
Surface Resistivity	3 X 10 ⁸			Z	Mohm	C93/35/90	ASTM D257
Tensile Modulus	Test at 23 C	Test at 100 C		X Y	MPa (kpsi)	A	ASTM D638
	1070 (156)	450 (65)					
	860 (125)	380 (55)					
ultimate stress	29 (4.2)	20 (2.9)		X	MPa (kpsi)	A	ASTM D695
	27 (3.9)	18 (2.6)		Y			
ultimate strain	6.0	7.2		X	%		
	4.9	5.8		Y			
Compressive Modulus	710 (103)	500 (73)		X	MPa (kpsi)	A	ASTM D695
	710 (103)	500 (73)		Y			
	940 (136)	670 (97)		Z			
ultimate stress	27(3.9)	22 (3.2)		X	MPa (kpsi)	A	ASTM D695
		21 (3.1)		Y			
	52 (7.5)	43 (6.3)		Z			
ultimate strain	8.5	8.4		X	%	A	ASTM D695
	7.7	7.8		Y			
	12.5	17.6		Z			
Deformation Under Load	Test at 150 C 1.0			Z	%	24 hr/14 MPa (2kpsi)	ASTM D621
Water Absorption Thickness = 0.8 mm (0.031) Thickness = 1.6 mm (0.062)	0.9 (0.02)				mg (%)	D24/23	ASTM D570
	13 (0.015)						
Specific Gravity	2.2						ASTM D792
Heat Distortion Temperature	>260 (>500)			X,Y	C (F)	1.82 MPa (264 psi)	ASTM D648
Specific Heat	0.96 (0.23)				J/g/K (BTU/lb/ F)		Calculated
Thermal Conductivity	0.20			Z	W/m/K		ASTM C518
Thermal Expansion	X	Y	Z	<<<	mm/m		ASTM D3386 (10K/min) (Values given are total change from a base temperature of 35 C)
	-6.1	-8.7	-18.7			-100 C	
	-0.9	-1.8	-6.9			15	
	-0.5	-0.9	-4.5			25	
	1.1	1.5	8.7			75	
	2.3	3.2	28.3			150	
	3.8	5.5	69.5			250	

[1] SI unit given first with other frequently used units in parentheses.

[2] References: Internal TR's 1430, 2224, 2854. Test were at 23°C unless otherwise noted. Typical values should not be used for specification limits.

RT/duroid® and DUROID® are licensed trademarks of ROGERS Corporation for its microwave laminates.

The above data represents typical values, not statistical minimums. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. The relative merits of materials for a specific application should be determined by your evaluation.

These products may require a validated export license issued by the United States Department of Commerce for export of these materials from the United States or Canada.

ROGERS
SINCE 1832

Rogers Corporation
Microwave Materials Division
100 S. Roosevelt
Chandler, AZ 85226-3415 U.S.A.
Tel: 480 961-1382
FAX: 480 961-4533
Toll Free: 877 643-7701
Website: <http://www.rogers-corp.com/mwu/>
ISO 9002 CERTIFIED

射频和天线设计培训课程推荐

易迪拓培训(www.edatop.com)由数名来自于研发第一线的资深工程师发起成立,致力并专注于微波、射频、天线设计研发人才的培养;我们于 2006 年整合合并微波 EDA 网(www.mweda.com),现已发展成为国内最大的微波射频和天线设计人才培养基地,成功推出多套微波射频以及天线设计经典培训课程和 ADS、HFSS 等专业软件使用培训课程,广受客户好评;并先后与人民邮电出版社、电子工业出版社合作出版了多本专业图书,帮助数万名工程师提升了专业技术能力。客户遍布中兴通讯、研通高频、埃威航电、国人通信等多家国内知名公司,以及台湾工业技术研究院、永业科技、全一电子等多家台湾地区企业。

易迪拓培训课程列表: <http://www.edatop.com/peixun/rfe/129.html>



射频工程师养成培训课程套装

该套装精选了射频专业基础培训课程、射频仿真设计培训课程和射频电路测量培训课程三个类别共 30 门视频培训课程和 3 本图书教材;旨在引领学员全面学习一个射频工程师需要熟悉、理解和掌握的专业知识和研发设计能力。通过套装的学习,能够让学员完全达到和胜任一个合格的射频工程师的要求...

课程网址: <http://www.edatop.com/peixun/rfe/110.html>

ADS 学习培训课程套装

该套装是迄今国内最全面、最权威的 ADS 培训教程,共包含 10 门 ADS 学习培训课程。课程是由具有多年 ADS 使用经验的微波射频与通信系统设计领域资深专家讲解,并多结合设计实例,由浅入深、详细而又全面地讲解了 ADS 在微波射频电路设计、通信系统设计和电磁仿真设计方面的内容。能让您在最短的时间内学会使用 ADS,迅速提升个人技术能力,把 ADS 真正应用到实际研发工作中去,成为 ADS 设计专家...



课程网址: <http://www.edatop.com/peixun/ads/13.html>



HFSS 学习培训课程套装

该套课程套装包含了本站全部 HFSS 培训课程,是迄今国内最全面、最专业的 HFSS 培训教程套装,可以帮助您从零开始,全面深入学习 HFSS 的各项功能和在多个方面的工程应用。购买套装,更可超值赠送 3 个月免费学习答疑,随时解答您学习过程中遇到的棘手问题,让您的 HFSS 学习更加轻松顺畅...

课程网址: <http://www.edatop.com/peixun/hfss/11.html>

CST 学习培训课程套装

该培训套装由易迪拓培训联合微波 EDA 网共同推出,是最全面、系统、专业的 CST 微波工作室培训课程套装,所有课程都由经验丰富的专家授课,视频教学,可以帮助您从零开始,全面系统地学习 CST 微波工作的各项功能及其在微波射频、天线设计等领域的设计应用。且购买该套装,还可超值赠送 3 个月免费学习答疑...

课程网址: <http://www.edatop.com/peixun/cst/24.html>



HFSS 天线设计培训课程套装

套装包含 6 门视频课程和 1 本图书,课程从基础讲起,内容由浅入深,理论介绍和实际操作讲解相结合,全面系统的讲解了 HFSS 天线设计的全过程。是国内最全面、最专业的 HFSS 天线设计课程,可以帮助您快速学习掌握如何使用 HFSS 设计天线,让天线设计不再难...

课程网址: <http://www.edatop.com/peixun/hfss/122.html>

13.56MHz NFC/RFID 线圈天线设计培训课程套装

套装包含 4 门视频培训课程,培训将 13.56MHz 线圈天线设计原理和仿真设计实践相结合,全面系统地讲解了 13.56MHz 线圈天线的工作原理、设计方法、设计考量以及使用 HFSS 和 CST 仿真分析线圈天线的具体操作,同时还介绍了 13.56MHz 线圈天线匹配电路的设计和调试。通过该套课程的学习,可以帮助您快速学习掌握 13.56MHz 线圈天线及其匹配电路的原理、设计和调试...

详情浏览: <http://www.edatop.com/peixun/antenna/116.html>



我们的课程优势:

- ※ 成立于 2004 年,10 多年丰富的行业经验,
- ※ 一直致力并专注于微波射频和天线设计工程师的培养,更了解该行业对人才的要求
- ※ 经验丰富的一线资深工程师讲授,结合实际工程案例,直观、实用、易学

联系我们:

- ※ 易迪拓培训官网: <http://www.edatop.com>
- ※ 微波 EDA 网: <http://www.mweda.com>
- ※ 官方淘宝店: <http://shop36920890.taobao.com>